



Saphir Plus

- The floor luminaire provides ideal direct and indirect illumination (about 36% direct light and 64% indirect light).
- The microprismatic diffuser ensures a pleasant and homogeneous light distribution on the work surface and avoids disturbing glare (UGR <17).
- The touch dimmer on the pole allows an independent control of direct and indirect light as well as stepless adjustment of the light intensity.
- Motion sensor: after 20 minutes absence the brightness reduces to 30%, after another 10 minutes the luminaire automatically switches off.
- Thanks to the daylight sensor, the brightness on the work area is recorded and the light intensity is adjusted according to the ambient light.
- 5 years warranty



Technical data

Power:	80 W
Weighted energy consumption:	80 kWh / 1000 h
Voltage:	200–240 VAC, 50 Hz
Luminous flux:	11000 Lumen, 4000 lm direct, 7000 lm indirect
Luminous efficacy:	137 Lumen / Watt
Colour temperature:	4000 Kelvin (neutral white), max. 3 MacAdam ellipses
Maximum illuminance:	1500 Lux (measuring distance 120 cm)
Colour rendering index (CRI):	> 80
UGR (Unified Glare Rating):	< 17
Life time:	50 000 hours
Stand-by power:	< 0.5 W
Height:	1950 mm
Base:	460 mm x 300 mm (L x W)
Head of lamp:	610 mm x 310 mm x 30 mm (L x Wx H)
Length of the cable:	2.0 m
Net weight:	13.4 kg
Material:	aluminium, steel, PS, PMMA
Packaging:	brown packaging with coloured label 1 parcel: 196 x 39 x 16 cm, 17.5 kg, girth: 306 cm
Light source:	energy efficiency class: D model identification: saphi0010030x

Item number:
41-5011.301.CH white
41-5011.302.CH anthracite

Interchangeability

The lighting source cannot be replaced. The construction of the luminaire does not allow the lighting source to be replaced, as there is a risk of damaging the luminaire.

styro ag
 Frauholzstrasse 27
 CH-6422 Steinen
 info@styro.ch
 www.styro.ch